

WHAT IS CLAIMED IS:

- Sub 1*
1. A method comprising the steps of:
generating WDM signal light by wavelength division
multiplexing a plurality of optical signals having
different wavelengths;
transmitting said WDM signal light by an optical
fiber transmission line; and
receiving said WDM signal light transmitted by said
optical fiber transmission line;
said receiving step comprising the steps of:
detecting chromatic dispersion related to at least
one of said plurality of optical signals; and
providing a variable dispersion compensator whose
chromatic dispersion and dispersion slope are controlled
so that said detected chromatic dispersion is reduced.
 2. A method according to claim 1, wherein said
detecting step comprises the steps of:
converting at least one of said plurality of
optical signals into an electrical signal; and
detecting the power of a frequency component in said
electrical signal corresponding to the bit rate of said
at least one optical signal.
 3. A method according to claim 1, wherein said
transmitting step comprises the step of providing a

linear repeating unit.

4. A method according to claim 3, wherein said transmitting step further comprises the steps of:

detecting chromatic dispersion related to at least one of said plurality of optical signals in said linear repeating unit; and

providing a variable dispersion compensator whose chromatic dispersion and dispersion slope are controlled so that said detected chromatic dispersion in said linear repeating unit is reduced.

5. A method according to claim 3, wherein said transmitting step further comprises the steps of:

detecting chromatic dispersion related to at least one of said plurality of optical signals in said linear repeating unit;

providing a variable dispersion compensator whose chromatic dispersion is controlled so that said detected chromatic dispersion in said linear repeating unit is reduced; and

providing a dispersion slope compensator for compensating dispersion slope in said linear repeating unit.

6. A method according to claim 1, wherein said generating step comprises the steps of:

detecting chromatic dispersion related to at least one of said plurality of optical signals;

providing a variable dispersion compensator whose chromatic dispersion is controlled so that said detected chromatic dispersion is reduced; and

providing a dispersion slope compensator for compensating dispersion slope.

7. A method comprising the steps of:

generating WDM signal light by wavelength division multiplexing a plurality of optical signals having different wavelengths;

transmitting said WDM signal light by an optical fiber transmission line; and

receiving said WDM signal light transmitted by said optical fiber transmission line;

said receiving step comprising the steps of detecting chromatic dispersion related to at least one of said plurality of optical signals;

providing a variable dispersion compensator whose chromatic dispersion is controlled so that said detected chromatic dispersion is reduced; and

providing a dispersion slope compensator for compensating dispersion slope.

8. A method according to claim 7, wherein said

detecting step comprises the steps of:

converting at least one of said plurality of optical signals into an electrical signal; and detecting the power of a frequency component in said electrical signal corresponding to the bit rate of said at least one optical signal.

9. A method according to claim 7, wherein said transmitting step comprises the step of providing a linear repeating unit.

10. A method according to claim 9, wherein said transmitting step further comprises the steps of:

detecting chromatic dispersion related to at least one of said plurality of optical signals in said linear repeating unit; and

providing a variable dispersion compensator whose chromatic dispersion and dispersion slope are controlled so that said detected chromatic dispersion in said linear repeating unit is reduced.

11. A method according to claim 9, wherein said transmitting step further comprises the steps of:

detecting chromatic dispersion related to at least one of said plurality of optical signals in said linear repeating unit;

providing a variable dispersion compensator whose

chromatic dispersion is controlled so that said detected chromatic dispersion in said linear repeating unit is reduced; and

providing a dispersion slope compensator for compensating dispersion slope in said linear repeating unit.

12. A method according to claim 7, wherein said generating step comprises the steps of:

detecting chromatic dispersion related to at least one of said plurality of optical signals;

providing a variable dispersion compensator whose chromatic dispersion is controlled so that said detected chromatic dispersion is reduced; and

providing a dispersion slope compensator for compensating dispersion slope.

13. A system comprising:

a transmitting terminal unit for generating WDM signal light by wavelength division multiplexing a plurality of optical signals having different wavelengths;

an optical fiber transmission line for transmitting said WDM signal light; and

a receiving terminal unit for receiving said WDM signal light transmitted by said optical fiber

transmission line;

said receiving terminal unit comprising:

a dispersion monitor for detecting chromatic dispersion related to at least one of said plurality of optical signals; a variable dispersion compensator; and

a circuit for controlling the chromatic dispersion and dispersion slope in said variable dispersion compensator so that said detected chromatic dispersion is reduced.

14. A system according to claim 13, wherein said dispersion monitor comprises a converter for converting at least one of said plurality of optical signals into an electrical signal, a bandpass filter for extracting a frequency component in said electrical signal corresponding to the bit rate of said at least one optical signal, and a power sensor for detecting the power of said frequency component.

15. A system comprising:

a transmitting terminal unit for generating WDM signal light by wavelength division multiplexing a plurality of optical signals having different wavelengths;

an optical fiber transmission line for transmitting said WDM signal light; and

a receiving terminal unit for receiving said WDM signal light transmitted by said optical fiber transmission line;

said receiving terminal unit comprising:

a dispersion monitor for detecting chromatic dispersion related to at least one of said plurality of optical signals; a variable dispersion compensator;

a circuit for controlling the chromatic dispersion in said variable dispersion compensator so that said detected chromatic dispersion is reduced; and

a dispersion slope compensator for compensating dispersion slope.

16. A system according to claim 15, wherein said dispersion monitor comprises a converter for converting at least one of said plurality of optical signals into an electrical signal, a bandpass filter for extracting a frequency component in said electrical signal corresponding to the bit rate of said at least one optical signal, and a power sensor for detecting the power of said frequency component.

Add
a1